

## METHOD AND SYSTEM FOR APPROVING A PASSWORD

## FIELD OF THE INVENTION

The present invention concerns a method as  
5 defined in the preamble of claim 1 and a system as defined in the preamble of claim 5 for approving a password.

## BACKGROUND OF THE INVENTION

10 It is a generally known practice to use a user identifier and a corresponding password as a key to accessing information systems. This improves the safety of information systems and prevents information from being accessed by parties for which it is not intended.  
15 A password is a given string which is used to identify a user who logs in to a system by giving his/her user identifier.

The person maintaining the information system may make a definition in the user identification system requiring that special characters be included in  
20 all passwords. Special characters are symbols not included in the basic alphabet. The use of special characters further improves data security because the larger the choice of characters for a password, the  
25 larger will be the number of character combinations to try and the more difficult will it be to break up the password.

In certain MMI systems (MMI, Man Machine Interface), a separate user profile is created for each  
30 user. The user profile defines e.g. which MML commands the user is authorised to execute, and it is associated with the user name. When the user issues a command, the system checks whether the session in question has the authority to execute that command.

35 In the above-mentioned user identification system, a problem is that the use of special charac-

ters in a password is either optional or obligatory for all users. However, in many information systems, it would be important to require of certain users that they use longer passwords including special characters. Such passwords are more difficult to break up. At present, it is not possible for a person maintaining a user identification system to define which users are required to include more special characters in their passwords than others.

The object of the present invention is to eliminate the drawbacks described above or at least to significantly alleviate them.

A specific object of the present invention is to disclose a new type of method and system for approval of a password corresponding to a user identifier.

#### BRIEF DESCRIPTION OF THE INVENTION

In the method of the present invention for approving a password in a user identification system, in which the user identifier is associated with a user profile, a definition is made for each user profile, specifying whether the password should include special characters. Special characters are characters belonging to a predefined subset in a total range of characters, which includes all available characters. According to the invention, data indicating whether the password should include a character belonging to a predefined subset of the total range of characters is added to the user profile.

In an embodiment of the method, data indicating the minimum number of characters belonging to a predefined subset in the total range of characters is added to the user profile. In this case, the user must use a password containing at least the minimum number of special characters. The number of special charac-

ters is preferably verified in the user identification system.

In an embodiment of the method, when a user changes his/her password, a check is performed before approval of the new password to verify whether the password contains at least the required number of characters belonging to a predefined subset in the total range of characters.

The system of the invention for approving a password in a user identification system in which a user identifier is associated with a user profile comprises an information system which a user can only access if the user identification system approves the user on the basis of the user identifier and password.

According to the invention, the user identification system comprises means for adding to the user profile a data item indicating the presence in the password of a character belonging to a predefined subset in a total range of characters. The total range of characters comprises all the available characters.

In an embodiment of the system, the user identification system comprises means for adding to the user profile a data item indicating a required minimum number of characters belonging to a predefined subset in the total range of characters. Means for comparing and verifying the number of characters belonging to a predefined subset in the total range of characters that are present in the password and the number of characters required in the user profile are preferably comprised in the user identification system.

Further, the system preferably also comprises means for checking the password to verify whether it contains the required number of characters belonging to a predefined subset in the total range of characters before a new password is approved when the password is to be changed.

The invention improves the data security of a MML system for those users whose user profile includes a setting requiring the use of many special characters. At the same time, for users who are only entitled to execute MML language commands of the lowest levels, a user profile can be set that does not require the use of special characters. This makes the password easier to remember and allows easier and faster access to the system.

The invention gives the person maintaining the user identification system a chance to decide which ones of the users are required to use special characters in their passwords and which ones are not.

#### 15 LIST OF ILLUSTRATIONS

In the following, the invention will be described in detail by the aid of a few examples of its embodiments, wherein

Fig. 1 presents an embodiment of the system of the invention, and

Fig. 2 presents a block diagram illustrating the operation of the embodiment according to Fig. 1.

#### DETAILED DESCRIPTION OF THE INVENTION

The system illustrated in Fig. 1 comprises a user interface 11 serving as a means of controlling an information system 12. The user of the user interface must have the authority to access the information system. This authority is checked in a user identification system 13, where the user is asked to give a user identifier and a password. A preferred system for the embodiment in this example is the Nokia DX 200 telephone switching system, which has an MML user interface and uses commands that are entered in the MML language. These means 11, 12, 13 are implemented in a

manner known in itself and they will therefore not be described here in greater detail.

The user identification system 13 comprises means 1 for adding to the user profile a data item indicating a character belonging to a predefined subset in the total range of characters. A data item indicating a minimum number of characters belonging to a predefined subset in the total range of characters is added to the user profile using means 2. Moreover, the user identification system comprises means 3 for modifying the user profile when the password is changed and means 4 for finding the required number of characters belonging to a predefined subset in the total range of characters before the password is approved. In the case of the example, these means 1, 2, 3, 4 are implemented via software.

In the following, the events in the example will be described step by step with reference to the operational block diagram in Fig. 2.

The user is asked to give a user identifier, which he/she enters via the user interface 11, block 21. The user identification system 13 verifies whether the user identifier entered has been stored in the user identification system, block 22. If the user identifier entered is unknown, then the procedure will go on to block 29, where the user is presented an error message and user identification is terminated. If the user identifier is found, then the procedure will be continued.

The user identification system 13 identifies the user profile by the user identifier and retrieves the stored information corresponding to the user profile, block 23. Based on this information, the user identification system knows the password corresponding to the user identifier, the length of the password and the minimum number of characters belonging to a predefined subset in the total range of characters that the

5

20

25

35

